

## CS-362WES EXCELLENT FOR TOUGH PRUNING OR LIMBING JOBS





5 Year domestic warranty/2 year commercial warranty not available in all markets. Check with your dealer for details.

For your safety, use appropriate protective gear in the working environment.



## **FEATURES & BENEFITS**



Engine	Dry Weight*	Output	Fuel Tank	Oil Tank	Guide Bar Length	Saw Chain Pitch	Gauge
Displacement (cm³)	(kg)	(kW/ps)	Capacity (L)	Capacity (L)	(cm)	(inch)	(inch)
35.8	3.8	1.5/2.0	0.32	0.23	30, 35, 40	3/8,1/4	0.050

## <COMFORTABLE OPERATION>

- // Improved durability by chrome plating
- // Narrower louver for preventing pine needle penetration.
- // Tool-less air filter cover for easy access.
- // Vibration reduction system for operator comfort .
- // ES starting system for reduced effort starting.
- // Side access chain tensioner for quick chain adjustment.
- // Light weight and slim body width for maneuverability and easy cutting.

## <RELIABILITY>

- // Inertia type chain brake for safety.
- // Integrated choke and fast idle with trigger release for easy starting.
- // Replaceable metal bumper spike for improved control.
- // Automatic clutch-driven oiler to keep chain lubricated













Without guide bar & saw chain

Specifications, descriptions, and illustrative materials in this literature are as accurate as known at the time of publication, but are subject to change without notice.

